

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE)
CB SCHEME

CB TEST CERTIFICATE

Product	AC/DC Power Module
Name and address of the applicant	ARCH ELECTRONICS CORP 3F, NO. 79, SEC1, HSIN TAI WU RD., HSI CHIH, NEW TAIPEI CITY, 221, TAIWAN
Name and address of the manufacturer	ARCH ELECTRONICS CORP 3F, NO. 79, SEC1, HSIN TAI WU RD., HSI CHIH, NEW TAIPEI CITY, 221, TAIWAN
Name and address of the factory	ARCH ELECTRONICS CORP. 3F, NO. 79, SEC1, HSIN TAI WU RD., HSI CHIH, NEW TAIPEI CITY, 221, TAIWAN
<i>Note: When more than one factory, please report on page 2</i>	<input type="checkbox"/> Additional Information on page 2
Ratings and principal characteristics	For model ATCH30-xS: 100-277Vac, 47-63Hz, 0.6A max. Or 100-250Vdc, 0.6A max. See test report for details.
Trademark / Brand (if any)	
Type of Customer's Testing Facility (CTF) Stage used	
Model / Type Ref.	AFCH25-xS-A2, AFCH25-xS-JST, AFCH25-xS, ATCH30-xS-A2, ATCH30-xS-JST, ATCH30-xS See Page 2
Additional information (if necessary may also be reported on page 2)	The report was revised to include technical modifications <input checked="" type="checkbox"/> Additional Information on page 2
A sample of the product was tested and found to be in conformity with	IEC 60950-1:2005/AMD1:2009, IEC 60950-1:2005/AMD2:2013, IEC 60950-1:2005
As shown in the Test Report Ref. No. which forms part of this Certificate	1909082-CB-M1 issued on 2020-01-16

This CB Test Certificate is issued by the National Certification Body



- UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnamesDate: 2020-02-05
Original Issue Date: 2019-03-28

Signature:

Jan-Erik Storgaard



Ref. Certif. No.

DK-82017-M1-UL

Model Details:

AFCH25-xS-A2,AFCH25-xS-JST,AFCH25-xS,ATCH30-xS-A2,ATCH30-xS-JST,ATCH30-xS (where "x" can be "3.82 to 5.35" or "9 to 12.6" or "11.25 to 15.75" or "18 to 25.2")

Additional Information:

Additionally evaluated to EN 60950-1:2006 /A11:2009 /A1:2010 /A12:2011 /A2:2013; National Differences specified in the CB Test Report.

The original report was modified to include the following changes/additions:

1. Alternate one PWB layout for ATCH30-xS and ATCH30-xS-A2.
2. Alternate one PWB layout for AFCH25-xS and AFCH25-xS-A2.
3. Alternate input rating 100-250Vdc, 0.49A for model AFCH25 series and 100-250Vdc, 0.6A for model ATCH30 series.
4. Alternate new Models AFCH25-xS-JST and ATCH30-xS-JST.

Additional information (if necessary)



UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/names

Date: 2020-02-05

Original Issue Date: 2019-03-28

Signature:

Jan-Erik Storgaard